

Frequently Asked Questions

Question

C A 8 D 8 : 0 F 8 O FreeBSD : > = A > ; 8 (KOI8-R 8 UTF-8)

Answer

0 A B @ > 9 : 0 KOI8-R :

```
vi /etc/rc.conf
    keymap="ru.koi8-r"
    font8x8="cp866-8x8"
    font8x14="cp866-8x14"
    font8x16="cp866b-8x16"
    scrnmap="koi8-r2cp866"
    cursor="destructive"
```

0 < 5 = 8 B L 2 A 5 cons25 = 0 cons25r 2 /etc/ttys:

```
vi /etc/ttys
:%s/cons25/cons25r/g
```

kill -HUP 1 (G B > 1 K ? 5 @ 5 G 8 B 0 ; A O /etc/ttys)

/etc/rc.d/syscons restart

pw usermod root -L russian

```
( 2 K ? > ; = 8 B L 4 ; O 2 A 5 E 8 < 5 = ? > ; L 7 > 2 0 B 5 ; 5 9 : > < C = C 6 5 =
@ C A A : 8 9 , 5 A ; 8 2 K E > 4 8 B 5 = 0 A 5 @ 2 5 @ B > ; L : > C 4 0 ; 5 == > ? >
ssh/telnet, B > < > 6 = > 2 K ? > ; = 8 B L B > ; L : > M B > B H 0 3 4 ; O = 0 A B @ > 9 : 8
? > 4 4 5 @ 6 : 8 @ C A A : > 3 > O 7 K : 0 KOI8-R 2 A 8 A B 5 < 5)
```

0 A B @ > 9 : 0 UTF-8 (4 ; O @ 0 1 > B K A C 4 0 ; 5 == > 3 > B 5 @ < 8 = 0 ; 0):

/etc/login.conf 4 > 1 0 2 ; O 5 <:

```
russian-utf8/Russian Users Accounts:
:charset=UTF-8:
:lang=ru_RU.UTF-8:
```

```
:lc_all=ru_RU.UTF-8:
:tc=default:
```

5 @ 5 A B @ 0 8 2 0 5 < : :

cap_mkdb /etc/login.conf

@ 8 : @ 5 ? ; O 5 < ? > ; L 7 > 2 0 B 5 ; O :

pw usermod ; > 3 8 = -L russian-utf8

> 1 0 2 ; O 5 < 2 /etc/profile

MM_CHARSET=UTF-8; export MM_CHARSET

; 5 : A 5 9 C A L : > 2 ? @ 5 4 A B 0 2 8 ; 8 = A B @ C : F 8 N
? > C A B 0 => 2 : 5 UTF-8 2 D 8 7 8 G 5 A : > 9 : > = A > ; 8 , ? @ 8 ? > < > I 8
C B 8 ; 8 B K jfbterm:

Jfbterm @ 0 1 > B 0 5 B G 5 @ 5 7 framebuffer, ? > 4 4 5 @ 6 8 2 0 5 B VESA- @ 0 7 @ 5 H 5 = 8 O 8 2 5 6
F 2 5 B > 2 ,
? > 7 2 > ; O 5 B ? > A B 0 2 8 B L 2 D > = B 5 @ < 8 = 0 ; 0 : 0 @ B 8 = : C , @ 0 1 > B 0 5 B
A < K H L N 8 B . 4 . > 1 I 5 < , : 0 G 0 5 < , A B 0 2 8 < 8 : > < ? 8 ; 8 < . (A ; 8 = 5
A : > < ? 8 ; O ; > A L , A B 0 2 8 < ? > A ; 5 4 = 8 9 autoconf 8 automake)

fetch

```
http://www.ac.auone-net.jp/~baba/jfbterm/jfbterm-FreeBSD-0.5.1.tar.gz
tar xvzf jfbterm-FreeBSD-0.5.1.tar.gz
cd jfbterm-FreeBSD-0.5.1
./configure CPPFLAGS=-I/usr/local/include LDFLAGS=-L/usr/local/lib
--prefix=/usr/local --mandir=/usr/local/man
/usr/local/bin/gmake
sudo /usr/local/bin/gmake install
```

K A B 0 2 ; O 5 < ? 0 @ 0 < 5 B @ K B 5 @ < 8 = 0 ; 0

```
cat /usr/local/share/jfbterm/termcap.jfbterm >>
/usr/share/misc/termcap
cap_mkdb /usr/share/misc/termcap
```

!>740Q< :>=D83

```
cp /usr/local/etc/jfbterm.conf.sample /etc/jfbterm.conf
```

0G05<8AB028<C=8:>4=K9H@8DB

```
fetch http://www.ac.auone-net.jp/~baba/gnu-unifont/unifont.pcf.gz
mkdir -p /usr/local/lib/X11/fonts/local/
cp unifont.pcf.gz /usr/local/lib/X11/fonts/local/
```

0?CA:0<(2B5@<8=0;5)

jfbterm

A;8UTF=5>B>1@0605BAO,B><5=O5<2:>=D835/etc/jfbterm.conf
AB@>G:C

encoding: locale =0 encoding: UTF-8

@8:@CB8BL22>4@CAA:8E1C:2<>6=>G5@57uim-m17nlib.

10.10.2008, 2B>@:Litos, AB>G=8::...

<http://ihtindr.info/>

;O C40;5==>3>B5@<8=0;L=>3>4>ABC?087A8AB5<K A UTF-8
;>:0;870F859:A8AB5<0<A locale>B;8G=>9>B UTF-8,<>6=>
2>A?>;L7>20BLAO CB8;8B>9luit:

?@8<5@8A?>;L7>20=8Oluit (man luit):

#luit-encoding "KOI8-R" slogin username@host.domain

2:0G5AB25encoding8A?>;L7>20BLcharsetA>>B25BAB2CN185
C40;5==><C locale,240==><?@8<5@5KOI8-R

Vampyr`s House!

<https://415.spb.ru/ins/faq/faq.php?0.cat.15>

! B @ 0 = 8 F 0 4/4

Details

Info Sunday 14 March 2010 - 18:35:40 by

Vampyr`s House!