

Frequently Asked Questions

Question

! < 5 = 0 IMEI

Answer

' 5 @ 5 7 8 = 6 5 = 5 @ = > 5 < 5 = N:

0 1 8 @ 0 5 < 2 B 5 ; 5 D > = 5 : * # # 3 6 4 6 6 3 3 # * # *
5 @ 5 E > 4 8 < = 0 2 : ; 0 4 : C Connectivity
K 1 5 @ 0 5 < : CDS Information > Radio Information > Phone 1
0 4 A B @ > : > 9 AT + 4 > ? 8 A K 2 0 5 < : EGMR = 1,7, " 2 0 H _ IMEI "
; O A < 5 = K IMEI = 0 2 B > @ C N SIM : 0 @ B C (5 A ; 8 5 A B L), ? > 2 B > @ O 5 <
? @ 5 4 K 4 C I 8 9 H 0 3, = > ? 8 H 5 < C 6 5 : EGMR = 1,10, " 2 0 H _ IMEI "
0 6 8 < 0 5 < : = > ? : C SEND AT 8 ? 5 @ 5 7 0 3 @ C 6 0 5 < A O.
A ; 8 = 5 ? > ; C G 0 5 B A O, B > ? > A ; 5 AT 8 ? 5 @ 5 4 + = C 6 = > ? > A B 0 2 8 B L
? @ > 1 5 ; .

! ? > < > H L N B 5 @ < 8 = 0 ; 0:

su

echo 'AT +EGMR=1,7, " (_IMEI)"> /dev/pttycmd1

" 0 : 6 5 5 A ; 8 C 2 0 A 4 2 C E A 8 < > G = K 9 0 ? ? 0 @ 0 B, B > 4 ; O A < 5 = K IMEI = 0
2 B > @ C N SIM = 0 4 > 4 > ? 8 A 0 B L:

echo 'AT +EGMR=1,10, " (_IMEI)"> /dev/pttycmd1

; O = 5 : > B > @ K E B 5 ; 5 D > = > 2 = 5 : 8 B 0 9 A : 8 E < 0 @ > : < > 6 5 B
? > < > G L 4 0 = = 0 O : > < < 0 = 4 0:

su

echo -e 'AT +EGMR=1,7, " (_IMEI)"> /dev/smd0

8 ; 8

su

echo -e 'AT +EGMR=1,10, " (_IMEI)"> /dev/smd11

; O B 5 ; 5 D > = > 2 HTC < > 6 5 B ? > < > G L 2 A B @ > 5 = = 0 O C B 8 ; 8 B 0

radiooptions:

radiooptions 13 'AT +EGMR=1,10, " (_IMEI)"

Vampyr`s House!

<https://415.spb.ru/ins/faq/faq.php?0.cat.75>

! B @ 0 = 8 F 0 2/2

Details

Info Saturday 27 May 2017 - 21:18:52 by vampyr

Vampyr`s House!